

COOKING LINES

KOCHSERIEN / COTTURA ORIZZONTALE
LIGNES DE CUISSON / LINEAS DE COCCIÓN



FOOD SERVICE EQUIPMENT
WORLDWIDE



SERIES 700 - GAS GRIDDLES

Cooking



Smooth plate



Chromed smooth plate



Ribbed plate



Chromed ribbed plate



2/3 smooth - 1/3 ribbed



Chromed
2/3 smooth - 1/3 ribbed

	Item Code Artikelnummer	Module Modul mm	Dimensions Abmessungen mm	Power Leistung kW	Heating Beheizung	Version Version	Power supply Netzspannung
	VS7040FTGV	400	400•730•250	6,0			-
	VS7040FTGVCRT	400	400•730•250	7,0			-
	VS7040FTRGV	400	400•730•250	6,0			-
	V7040FTRGVCRT	400	400•730•250	7,0			-
	VS7080FTGV	800	800•730•250	12,0			-
	VS7080FTGVCRT	800	800•730•250	14,0			-
	VS7080FTRGV	800	800•730•250	12,0			-
	V7080FTRGVCRT	800	800•730•250	14,0			-



- The Series 700 griddles, are the best for performance and cleaning. The cooking plate can be of chrome-plated (thickness 70µ) or mild steel. The cooking surface is welded on the pressed worktop, has rounded corners, high uniformity of heat distribution.

- Pressed working top in stainless steel AISI 304, 20/10 thick.
- Available with smooth, ribbed or 2/3 smooth 1/3 ribbed surface.
- Pilot burners with piezoelectric lighting
- Gas regulation with safety tap equipped with thermocouple.
- Chromed models equipped with thermostatic valve.

Accessories

VS7040B

Open stand
400 mm



VS7080B

Open stand
800 mm




H2 CABINETS

R22


VS7040PSFTS

Splash guard for
griddle plates
VS7040FT...V...



VS7080PSFTS

Splash guard for
griddle plates
VS7080FT...V...



V40PDX

Right door for
stand 400 mm



V40PSX

Left door for stand
400 mm



V80P

Double door for
stand 800 mm



Z/M95109400

Teflon plug



Optionals

Has to be assembled directly in production

VS40TR

Thermostatic version
for 400 mm non
chromed modules



VS80TR

Thermostatic version
for 800 mm non
chromed modules





Cooking

SERIES 700 - ELECTRIC GRIDDLES



Smooth plate




Chromed smooth plate



Ribbed plate



Chromed ribbed plate



2/3 smooth - 1/3 ribbed



Chromed
2/3 smooth - 1/3 ribbed

	Item Code Artikelnummer	Module Modul mm	Dimensions Abmessungen mm	Power Leistung kW	Heating Beheizung	Version Version	Power supply Netzspannung
	VS7040FTEVT	400	400•730•250	5,4			380 - 415 V 3+N 50-60 Hz
	VS7040FTEVCRT	400	400•730•250	5,4			380 - 415 V 3+N 50-60 Hz
	VS7040FTREVT	400	400•730•250	5,4			380 - 415 V 3+N 50-60 Hz
	V7040FTREVCRT	400	400•730•250	5,4			380 - 415 V 3+N 50-60 Hz
	VS7080FTEVT	800	800•730•250	10,8			380 - 415 V 3+N 50-60 Hz
	VS7080FTEVCRT	800	800•730•250	10,8			380 - 415 V 3+N 50-60 Hz
	VS7080FTREVT	800	800•730•250	10,8			380 - 415 V 3+N 50-60 Hz
	V080FTREVCRT	800	800•730•250	10,8			380 - 415 V 3+N 50-60 Hz



- The Series 700 griddles, are the best for performance and cleaning. The cooking plate can be of chrome-plated (thickness 70µ) or mild steel. The cooking surface is welded on the pressed worktop, has rounded corners, high uniformity of heat distribution.

- Pressed working top in stainless steel AISI 304, 20/10 thick.
- Available with smooth, ribbed or 2/3 smooth 1/3 ribbed surface.
- Heavy-duty heating elements. Cooking temperature monitored by thermostats. Models equipped with safety thermostat.



Accessories

VS7040B

Open stand
400 mm



VS7080B

Open stand
800 mm



H2 CABINETS

R22



VS7040PSFTS

Splash guard for
griddle plates
VS7040FT..V...



VS7080PSFTS

Splash guard for
griddle plates
VS7080FT..V...



V40PDX

Right door for
stand 400 mm



V40PSX

Left door for stand
400 mm



V80P

Double door for
stand 800 mm



Z/M95109400

Teflon plug





Cooking

SERIES 700 - WATER GRILLS



- The Serie 700 of water grills is available in gas or electric version with free-standing modules of 400 mm and 800 mm.
- Grid in stainless steel rods.
Reversible cast-iron cooking grid sloped version for cooking fat meats and with drip tray for grease collection, plane version for fish and vegetables with circular elements on request.
- 3 sides splashguard in AISI 304 stainless steel, and removable grease collection tray, water fillable for easy cleaning. Evaporation of water grants the tenderness of the grilled food.
- Electric models: armored heating elements in incoloy installed under the cooking grid.
- Gas models: heating by steel burner located under the cooking grid.

Accessories

VS7040GGACQ

Reversible cast iron grill meat / fish for 400 mm modules



VS7080GGACQ

Reversible cast iron grill meat / fish for 800 mm modules



	Item Code Artikelnummer	Module Modul mm	Dimensions Abmessungen mm	Power Leistung kW	Version Version	Heating Beheizung	Accessories Zubehör	Power supply Netzspannung
	VS7040GRACQG	400	400•730•870	7,5	Grid in stainless steel rods		2 pieces required VS7040GGACQ	-
	VS7080GRACQG	800	800•730•870	15,0	Grid in stainless steel rods		4 pieces required VS7080GGACQ	-
	VS7040GRACQE	400	400•730•870	6,0	Grid in stainless steel rods		2 pieces required VS7040GGACQ	380 - 415 V 3+N 50-60 Hz
	VS7080GRACQE	800	800•730•870	12,0	Grid in stainless steel rods		4 pieces required VS7080GGACQ	380 - 415 V 3+N 50-60 Hz

SERIES 700 - LAVA-STONE GRILLS



- The Serie 700 of lava-stone grills is equipped with a Piezo ignition system. Available with one or two independent cooking zones.
- Grid in stainless steel rods.
- Reversible cast-iron cooking grid sloped version for cooking fat meats, plane version for fish and vegetables on request.
- Grills are equipped with a grid lifting device by mechanical levers to space the grid from the brazier.



Item Code Artikelnummer	Module Modul mm	Dimensions Abmessungen mm	Power Leistung kW	Version Version	Heating Beheizung	Equipped with Ausgestattet mit	Power supply Netzspannung
 VS7040GRL	400	400•730•870	7,5	V shaped stainless steel grid		1 grid	-
 VS7080GRL	800	800•730•870	15	V shaped stainless steel grids		2 grids	-

Accessories

VS70GGGRL

Cast iron grill



V40PDX

Right door for
stand 400 mm



V40PSX

Left door for stand
400 mm



V80P

Double door for
stand 800 mm



Z/ELAVA07KG

Lava-stone
bag 7 kg





Cooking

SERIES 700 - REFRIGERATED UNDERCOUNTERS



HCE2016 + Z/FB00AY255 + 3 x Z/CU700

Item Code Artikelnummer	Working Temperature Arbeitstemperatur °C	Capacity Kapazität GN	Absorbed Power Anschlusswert Watt	Dimensions Abmessungen mm	Stainless Steel Type Edelstahl AISI	Insulation Thickness Isolierung mm
----------------------------	------------------------------------------------	-----------------------------	-----------------------------------------	---------------------------------	----------------------------------------	------------------------------------------



BNA0080	-2°/+8°	1 x GN2/1	1100	1200•700•600	304	50
BNB0040	-10°/-20°	1 x GN2/1	1100	1200•700•600	304	50



HCE2014	-2°/+8°	2 x GN 1/1	170	1200•700•600	304	50
----------------	---------	------------	-----	--------------	-----	----



HCE2016	-2°/+8°	3 x GN 1/1	500	1600•700•600	304	50
----------------	---------	------------	-----	--------------	-----	----



HCE2018	-2°/+8°	4 x GN 1/1	510	2200•700•600	304	50
----------------	---------	------------	-----	--------------	-----	----



Accessories

Z/CU700

2 x 1/2
h=100 mm



! Only for positive counters

Z/FB00AY255





Set of 6 wheels with and without brakes (2+4)





Refrigerant Gas Kühlgas	Power Supply Netzspannung
R290	220 - 240 V 1+N 50 Hz
R290	220 - 240 V 1+N 50 Hz
R290	220 - 240 V 1+N 50 Hz
R290	220 - 240 V 1+N 50 Hz
R290	220 - 240 V 1+N 50 Hz






SERIES 700 - GENERAL ACCESSORIES

Version Version	Item Code Artikelnummer	Description Beschreibung
	VS7040B	Open stand 400 mm
	VS7040BH2	Open stand 400 mm H2 R22
	VS7080B	Open stand 800 mm
	VS7080BH2	Open stand 800 mm H2 R22
	VS70120B	Open stand 1200 mm
	V40PDX	Right door for stand 400 mm
	V40PSX	Left door for stand 400 mm
	V80P	Double door for stand 800 mm
	V120P	Set of 3 doors for stand 1200 mm
	VKC11	Set of 2 drawers GN 1/1 for 400 mm modules, h=225 mm
	VKC21	Set of 2 drawers GN 2/1 for 800 mm modules, h=225 mm
	VRG11	Set of tray slides GN 1/1 for 6 grids
	VRG21	Set of tray slides GN 2/1 for 6 grids
	VKR22	Set of 2+2 wheels with brake (only suitable for freestanding models)
	Z/MER40	Heating group for cabinet 40 cm Power 2 kW, 220-240 V 50-60 Hz
	Z/MER80	Heating group for cabinet 80 cm Power 2 kW, 220-240 V 50-60 Hz
	Z/MPH50	Lowered foot H 50 mm for installation on hollow masonry base
	VGZ	Plinth junction

Version Version	Item Code Artikelnummer	Description Beschreibung
	VS70PLDX	Side panel for back to back equipment, right side
	VS70PLSX	Side panel for back to back equipment, left side
	VS140PL	Side panel for back to back equipment VS700 - 1400 mm
	V40ZFT	Front plinth for 400 mm module top.
	V80ZFT	Front plinth for 800 mm module top.
	V120ZFT	Front plinth for 1200 mm module top.
	V70ZLT	Side plinth for 700 mm module top.
	V40ZF	Front plinth for 400 mm module.
	V80ZF	Front plinth for 800 mm module.
	V120ZF	Front plinth for 1200 mm module.
	V160ZF	Front plinth for 1600 mm module.
	V200ZF	Front plinth for 2000 mm module.
	V240ZF	Front plinth for 2400 mm module.
	V70ZL	Side plinth.700 mm
	V140ZLP	Pass- through side plinth 1400 mm.
	VS70PLQDX	Squared side panel for back to back equipment, right side
	VS70PLQSX	Squared side panel for back to back equipment, left side
	VS140PLQ	Squared side panel for back to bwack equipment VS700 - 1400 mm
	VS40PRCAM	Flue extension 400 mm
	VS80PRCAM	Flue extension 800 mm
	VS120PRCAM	Flue extension 1200 mm
	VKSP40	Bridge system supports 40 l
	VKSP80	Bridge system supports 80 l
	VKSP100	Bridge system supports 100 l
	VKSP120	Bridge system supports 120 l
	VKSP160	Bridge system supports 160 l
	VS7040PSFTS	Splash guard for griddle plates VS7040FT...V...
	VS7080PSFTS	Splash guard for griddle plates VS7080FT...V...
	Z/GSFT	Scarper for smooth plate
	VRASFTR	Scarper for ribbed plate



SERIES 700 - GENERAL ACCESSORIES

Version Version	Item Code Artikelnummer	Description Beschreibung
	VS70PL1F	Flate plate, 1 burner Dim [mm]: 390 • 284 • 22
	Z/MCASB	Water tap to be fixed on the side or on the top of neutral modules (In the order please specify the model of the equipment the water tap is to be fixed on - if it is not a neutral module please specify the side)
	VSPT15Q	Tray holder structure + column L= 1000÷1500
	VSPT20Q	Tray holder structure + column L= 1500÷2000
	VSPT25Q	Tray holder structure + column L= 2000÷2500
	VSPT30Q	Tray holder structure + column L= 2500÷3000
	VSPT35Q	Tray holder structure + column L= 3000÷3500
	VSPT40Q	Tray holder structure + column L= 3500÷4000
	VSPT45Q	Tray holder structure + column L= 4000÷4500
	VSPT50Q	Tray holder structure + column L= 4500÷5000
	VSPTSAL11	Price increase for integration of electric salamander support GN 1/1 on tray holder structure. Dimensions 380x450 mm
	VSS11	Support for electric salamander GN 1/1
	VPES	Schuko electrical socket with cover IP 44